



# Auto-Out® for “Flat Mesh” Style Venthoods



## For Residential Cooktops with “Flat Mesh” Style Venthoods

Product Name
Auto-Out® for “Flat Mesh” Style Venthoods
Model Number
AOV-T
Application
Residential, gas or electric, cooktops with “flat mesh” style venthoods overhead
Features/Benefits
<ul style="list-style-type: none"> <li>• Quick, easy, and secure installation</li> <li>• Smothers cooking fires at the source</li> <li>• Actuated by the flames of the fire</li> <li>• Works 24-7</li> <li>• Does not use batteries</li> <li>• Not pressurized</li> </ul>
Quantity Needed
One set of two for standard four-burner cooktops
Height Requirements
Measure to ensure there is between 24 - 32” from the cooktop to the bottom of venthood
Installation Method
Securely clips into venthood using bracket
Dimensions & Weight: One Unit
<ul style="list-style-type: none"> <li>• Weight: .958 lbs.</li> <li>• Length: 15”</li> <li>• Width: 3.5”</li> <li>• Height: 2.8”</li> </ul>

Intended Use
Small residential cooking fires, including grease fires (not intended to suppress fires caused by “deep-fat” frying)
Certification & Testing
<ul style="list-style-type: none"> <li>• Canister containing suppression agent has been tested by Southwest Research Institute® (SWRI), a Nationally Recognized Testing Laboratory (NRTL)</li> <li>• Suppression agent subject to national lab test standard for “Dry Chemical Fire Extinguishers”</li> </ul>
Product Life
6 years from the date of manufacture
Activation Method
Triggered by the flames of the fire (neither steam, smoke, nor heat alone will actuate the device)
Primary Suppression Agent
Siliconized dry chemical powder (sodium bicarbonate base) subject to national lab test standard for “Dry Chemical Fire Extinguishers”
Dispersal Method
Non-pressurized, gravity aided device
Clean-Up
Use a damp towel to sweep up the environmentally-friendly powder
Country of Manufacture
United States of America

1911 Windsor Place  
 Fort Worth, TX 76110  
 817-924-1370  
 sales@auto-out.com  
 www.Auto-Out.com